



座数/CKT	製品番号/PARTS No	A	B	C	D	E
4	9686S-04Y902	3.6	9.9			
5	-05	4.1	10.4			
6	-06	4.6	10.9			
7	-07	5.1	11.4			
8	-08	5.6	11.9			
9	-09	6.1	12.4			
10	-10	6.6	12.9			
11	-11	7.1	13.4	24.0	11.5	21.5
12	-12	7.6	13.9			
13	-13	8.1	14.4			
14	-14	8.6	14.9			
15	-15	9.1	15.4			
16	-16	9.6	15.9			
17	-17	10.1	16.4			
18	9686S-18Y902	10.6	16.9			

- NOTE
- 梱包数量/UNIT QUANTITY: 3000
 - リードテープ長さ/LEAD TAPE LENGTH
 - 560MIN カバーテープ リーダー部 COVER TAPE STARTING
 - 160MIN 部品挿入部 PARTS FILLING PORTION
 - 100MIN リーダー部/STARTING
 - カバーテープの剥離強度/COVER TAPE PEELING FORCE : 0.2~1.3N.
 - 10°
 - 製品引き出し方向 PRODUCT WITHDRAWAL DIRECTION
 - 9686S-10Y902に使用するエンボスは、K-9631S-1200になります。 EMBOSS USED FOR 9686S-10Y902 IS SET TO K-9631S-1200.



MATERIAL 材質				GENERAL TOLERANCES 一般公差		SCALE 尺度		UNIT 単位		TITLE 名称	
① カバーテープ/COVER TAPE: PET-TYPE ② キャリアテープ/CARRIER TAPE: A-PET ③ リール/REEL: PS (黒/BLACK)				DIM 寸法 ± 0.3 ANGLE 角度 ±		/		mm		SERIES 9686 SOCKET TAPING PRODUCT 9686シリーズ ソケット エンボス 梱包品	
FINISH 仕上げ				3RD. ANG. PROJ. 三角法		DR 08-10-9 Setchi chin CHK 08-10-9 M. TAKAGI		DSN 05-10-22 Y. Yoshikawa APP 08-10-9 Y. Yoshikawa		EDP No	
						IRISO ELECTRONICS CO., LTD. イリソ電子工業株式会社				PARTS No 部番 9686S-***Y902	
3000 REVISION S L M7 08-10-9										DWG No 図番 IMSA-9686S-***Y902	
LTR 記号	ECN NO	REVISION 記	DR	CHK	DATE 年月日					REV. 2	

DO NOT SCALE DRAWING. THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO IRISO AND SHOULD NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM.